## NSN 6625-00-993-0883

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-993-0883

Overall Length:
24.000 inches
Overall Height:
16.000 inches
Overall Width:
13.000 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 400.0 hertz
Accessory Components And Quantity:
Adapter, post 1, cord, power 1, filter, light 1, probe, attenuation 2
Voltage Rating:
125.0 volts
Beam Quantity:
1
Screen Size:
5 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Vertical and horizontal
Sweep Frequency Range:
+84.0/+100000.0 hertz
Single Trigger Sweep Duration:
1.0 milliseconds
Trigger Sweep Voltage Amplitude Rating:
100.0 volts
Trigger Sweep Polarity Switch:
Included
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
5.0 millivolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:
200.0 millivolts any acceptable outside diameter
Input Intensity Modulation Feature:

Not provided

## NSN 6625-00-993-0883

Oscilloscope - Page 2 of 2



Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
7.0 volts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Rating:
30.0 volts rms per inch
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 5.0 hertz and 240000.0 hertz
Y-axis Frequency Response Rating:
Between 5.0 hertz and 30000000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Z-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Precious Material:
Silver
Fsc Application Data:
Oscilloscope, except specially designed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-g