NSN 6625-00-993-3169

Ammeter - Page 1 of 2

Dc

Material: Plastic

Style Designator:Rectangular flush mtg

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-993-3169

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.740 inches |
| Overall Width: |
| 1.740 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.500 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Measurement Range: |
| -50.0/+50.0 microamperes, dc single indicator single range |
| Mounting Stud Diameter: |
| |
| 0.112 inches |
| 0.112 inches Movement Suspension Method: |
| |
| Movement Suspension Method: |

NSN 6625-00-993-3169

Ammeter - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0