

View Online at <https://aerobasegroup.com/nsn/6625-00-993-3466>

Circuit Current For Which Designed:

Ac

Overall Length:

3.016 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

Between 55.0 hertz and 75.0 hertz

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

21

Accuracy In Percent:

-0.3/+0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.125 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+75.0 hertz single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Power requirements: 2 watts ; operating temperature minus 65 to plus 85 degrees centigrade

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0