## NSN 6625-00-994-1774

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-994-1774

	ircuit Current For Which Designed:
Do	
Di	electric Withstanding Voltage In Volts:
-	500.0
<b>0</b> ۱	verall Length:
	625 inches
Ce	enter To Center Distance Between Mounting Facilities Parallel To Length:
Be	etween 1.304 inches and 1.320 inches
Ce	enter To Center Distance Between Mounting Facilities Parallel To Width:
Be	etween 1.304 inches and 1.320 inches
0	verall Height:
Зе	etween 1.734 inches and 1.766 inches
O١	verall Width:
Be	etween 1.734 inches and 1.766 inches
Mo	ounting Hole Diameter:
0.1	125 inches
Sc	cale Division Quantity:
10	) single indicator single range
Er	nvironmental Protection:
Sŀ	nock resistant and vibration resistant
Fu	urnished Items And Quantity:
Nι	ut 4; washer 4
n	dicator Type:
Di	al w/pointer
n	stallation Design:
Pa	anel
M	ounting Arrangement Style:
Fc	bur hole/stud rectangular/square
Di	al Scale Marking Color:
Bl	ack single indicator single range and yellow single indicator single range
Ac	ccuracy In Percent:
-3	.0/+3.0 at full scale single indicator single range
Ur	nable To Decode:
Ur	nable to decode or unable to decode
Me	eter Depth Behind Mounting Flange:
1.(	000 inches
Me	eter Body Diameter Behind Mounting Flange:
1.{	510 inches
M	ovement Type:
	oving coil, permanent magnet
	ackground Color:

## NSN 6625-00-994-1774

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-50.0/+50.0 milliamperes, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Yellow band from 5 to 0 to 5 ma and green from 20 to 30 ma on rightside of scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0