

View Online at <https://aerobasegroup.com/nsn/6625-00-995-2053>

Circuit Current For Which Designed:

Ac

Overall Length:

2.180 inches

Mounting Hole Diameter:

0.141 inches

Frequency Rating:

400.0 hertz

Overall Diameter:

3.500 inches

Environmental Protection:

Cold resistant and submersible and vibration resistant and watertight

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg screws nuts lockwashers 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.405 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Degrees; 0; 20; 25; 30; 35; 40; 45; 50

Mounting Facility Type And Quantity:

1 flange and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

12.0 ac

Phase:

Single

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0