

View Online at <https://aerobasegroup.com/nsn/6625-00-995-2054>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.180 inches

**Mounting Hole Diameter:**

0.141 inches

**Scale Division Quantity:**

8 single indicator single range

**Frequency Rating:**

400.0 hertz

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Cold resistant and submersible and vibration resistant and watertight

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Mtg screws nuts lockwashers 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

1000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.405 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Ft x 1000; 0; 30; 60; 90; 120

**Mounting Facility Type And Quantity:**

1 flange and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

12.0 ac

**Phase:**

Single

**Special Features:**

Ruggedized

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**FiiG:**

A310a0