NSN 6625-00-995-3784

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-995-3784

Circuit Current For Which Designed: Dc Dielectric Withstanding Voltage In Volts: 3000.0 Overall Length: 2.315 inches Mounting Hole Diameter: 0.150 inches Scale Division Quantity:
Dielectric Withstanding Voltage In Volts: 3000.0 Overall Length: 2.315 inches Mounting Hole Diameter: 0.150 inches
Overall Length: 2.315 inches Mounting Hole Diameter: 0.150 inches
Overall Length: 2.315 inches Mounting Hole Diameter: 0.150 inches
2.315 inches Mounting Hole Diameter: 0.150 inches
Mounting Hole Diameter: 0.150 inches
0.150 inches
Scale Division Quantity:
Scale Division Quantity.
30 single indicator single range
Overall Diameter:
3.500 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.190 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-995-3784Arbitrary Scale Meter - Page 2 of 2



Scale Marking:
0; 10; 20; 30
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/12, type mr36w100dcuar except as noted on drawing
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0