

View Online at <https://aerobasegroup.com/nsn/6625-00-995-3884>

Circuit Current For Which Designed:

Dc

Overall Length:

2.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.870 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.870 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Mounting Stud Length:

0.562 inches

Furnished Items And Quantity:

Nut 8; washer 6; light bulb 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.469 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+200.0 watts single indicator 2nd range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Knife edge pointer and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Light bulbs use 6.3 v 0.15 amp power

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0