NSN 6625-00-995-4774

Ammeter - Page 1 of 2

Scale Division Quantity:

Overall Diameter:

2.690 inches

25 single indicator single range

Dc

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-995-4774

Mounting Bolt Circle Diameter:
2.050 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.380 inches
Meter Body Diameter Behind Mounting Flange:
2.050 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Mounting Facility Type And Quantity:
3 threaded stud
3 threaded stud Measurement Range:
Measurement Range:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post Nuclear Hardness Critical Feature:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post Nuclear Hardness Critical Feature: Nonhardened
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post Nuclear Hardness Critical Feature: Nonhardened Style Designator:
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg
Measurement Range: +0.0/+5.0 milliamperes, dc single indicator single range Mounting Stud Diameter: 0.112 inches Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 binding post Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Reference Number Differentiating Characteristics:

NSN 6625-00-995-4774

Ammeter - Page 2 of 2



			ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0