NSN 6625-00-996-4105

Modulation Meter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-996-4105

Dc
Dielectric Withstanding Voltage In Volts:
500.0
Overall Length:
2.496 inches
Overall Height:
0.781 inches
Overall Width:
1.875 inches
Scale Division Quantity:
20 single indicator single range
Environmental Protection:
Dust tight
Barrel Width:
1.600 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Sensitivity Rating:
200.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.705 inches
Meter Body Width Behind Mounting Flange:
1.600 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
1 bracket and 1 flange and 4 screw

NSN 6625-00-996-4105

Modulation Meter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-100.0/+100.0 kilohertz single indicator single range
Scale Selection Method:
Terminal
Meter Body Height Behind Mounting Flange:
0.965 inches
Meter Barrel Depth:
1.622 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Measures kilocycles deviation
Material:
Plastic and steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg barrel, left
Supplementary Features:
2.0 seconds maximum response time
Unit Of Issue Weight:
0.25 pounds
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0