

View Online at <https://aerobasegroup.com/nsn/6625-00-996-4105>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

2.496 inches

Overall Height:

0.781 inches

Overall Width:

1.875 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Dust tight

Barrel Width:

1.600 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.705 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 1 flange and 4 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-100.0/+100.0 kilohertz single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

0.965 inches

Meter Barrel Depth:

1.622 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Measures kilocycles deviation

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, left

Supplementary Features:

2.0 seconds maximum response time

Unit Of Issue Weight:

0.25 pounds

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0