

View Online at <https://aerobasegroup.com/nsn/6625-00-996-7623>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

2.079 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

20 single indicator 2nd range

Overall Diameter:

4.500 inches

Mounting Bolt Circle Diameter:

4.124 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.438 inches

Meter Body Diameter Behind Mounting Flange:

3.594 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+3.0 volts, ac single indicator 1st range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Markings:

On rear of meter: positive terminal has plus sign; fs 200uadc for sensitivity; + 50 ohms for coil resistance

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance: 400 to 500 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0