

View Online at <https://aerobasegroup.com/nsn/6625-00-996-7623>

**Circuit Current For Which Designed:**

Ac and dc

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Overall Length:**

2.079 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

20 single indicator 2nd range

**Overall Diameter:**

4.500 inches

**Mounting Bolt Circle Diameter:**

4.124 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.438 inches

**Meter Body Diameter Behind Mounting Flange:**

3.594 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+3.0 volts, ac single indicator 1st range

**Features Provided:**

Knife edge pointer and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder stud

**Special Markings:**

On rear of meter: positive terminal has plus sign; fs 200uadc for sensitivity; + 50 ohms for coil resistance

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Internal resistance: 400 to 500 ohms

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0