NSN 6625-00-996-9856

S-units Meter - Page 1 of 2

Dial scale inscribed signal strength



View Online at https://aerobasegroup.com/nsn/6625-00-996-9856

Circuit Current For Which Designed:				
Dc				
Overall Length:				
1.290 inches				
Center To Center Distance Between Mounting Facilities Parallel To Length:				
1.320 inches				
Center To Center Distance Between Mounting Facilities Parallel To Width:				
1.320 inches				
Overall Height:				
1.760 inches				
Overall Width:				
1.760 inches				
Scale Division Quantity:				
10 single indicator single range				
Mounting Stud Length:				
0.530 inches				
Furnished Items And Quantity:				
Washer6, nut 6				
Indicator Type:				
Dial w/pointer				
Installation Design:				
Panel				
Mounting Arrangement Style:				
Four hole/stud rectangular/square				
Accuracy In Percent:				
-2.0/+2.0 at full scale single indicator single range				
Meter Depth Behind Mounting Flange:				
0.870 inches				
Meter Body Diameter Behind Mounting Flange:				
1.500 inches				
Movement Type:				
Moving coil, permanent magnet				
Scale Graduation Type:				
Linear single indicator single range				
Measurement Range:				
+0.0/+10.0 s-units single indicator single range				
Features Provided:				
Zero adjuster				
Movement Suspension Method:				
Jewel pivot base				
Special Markings:				

NSN 6625-00-996-9856

S-units Meter - Page 2 of 2



Nuclea	r Hardness	Critical	Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0