

View Online at <https://aerobasegroup.com/nsn/6625-00-997-3156>

Circuit Current For Which Designed:

Ac and dc

Scale Division Quantity:

25 single indicator 1st range 25 single indicator 4th range 50 single indicator 5th range 50 single indicator 6th range

Indicator Type:

Dial w/pointer

Dial Scale Marking Color:

Green single indicator 1st range black single indicator 2nd range and red single indicator 2nd range black single indicator 3rd range green single indicator 4th range black single indicator 6th range red all indicators 5th range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Scale Graduation Type:

Linear single indicator 1st range linear single indicator 4th range linear single indicator 5th range linear single indicator 6th range

Measurement Range:

+0.0/+10.0 amperes single indicator 1st range -20.0/+10.0 decibels single indicator 2nd range +0.0/+2.0 megohms single indicator 3rd range +0.0/+10.0 microamps single indicator 4th range +0.0/+250.0 volts, ac single indicator 5th range +0.0/+250.0 volts, dc single indicator 6th range

Features Provided:

Zero adjuster

Meter Replacement Type:

Multimeter

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

8 banana plug

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Fsc Application Data:

Elec, elect, properties measuring and test instrumens

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0