

View Online at <https://aerobasegroup.com/nsn/6625-00-998-0061>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.210 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.861 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.502 inches

**Overall Height:**

3.750 inches

**Overall Width:**

3.300 inches

**Mounting Stud Length:**

0.434 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

10.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges and red single indicator all ranges

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.960 inches

**Meter Body Diameter Behind Mounting Flange:**

2.690 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Bot scale: 0, 1, 2, 3, 4, 5; top scale: 0, 2, 4, 6, 8, 10

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Knife edge pointer and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Top scale: 0 to one red band, null at line 5, bot scale: 0 to 0.5 red band, cal at line 4

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Chromate

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0