

View Online at <https://aerobasegroup.com/nsn/6625-00-998-0061>

Circuit Current For Which Designed:

Dc

Overall Length:

1.210 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.861 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.502 inches

Overall Height:

3.750 inches

Overall Width:

3.300 inches

Mounting Stud Length:

0.434 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

10.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges and red single indicator all ranges

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.960 inches

Meter Body Diameter Behind Mounting Flange:

2.690 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Bot scale: 0, 1, 2, 3, 4, 5; top scale: 0, 2, 4, 6, 8, 10

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Mounting Stud Diameter:

0.138 inches

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Top scale: 0 to one red band, null at line 5, bot scale: 0 to 0.5 red band, cal at line 4

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0