

View Online at <https://aerobasegroup.com/nsn/6625-00-998-0780>

**Overall Length:**

18.375 inches

**Wattage Rating In Watts:**

80.0

**Overall Height:**

5.219 inches

**Overall Width:**

19.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Accessory Component Quantity:**

1 and 1

**Electrical Connection Type:**

Bnc

**Accessory Controlling Agency:**

Hewlett-packard col Hewlett-packard co

**Accessory Identifying Number:**

H96-5245I model no. And 52538 model no.

**Internal Battery Accommodation:**

Not included

**Voltage Rating:**

115.0 volts or 230.0 volts

**Output Frequency Rating:**

Between 1.0 hertz and 10000000.0 hertz

**Electrical Connection Quantity:**

7

**Mounting Method:**

Rack and bench

**Accessory Component Name:**

Electronic counter! Frequency converter

**Measurement Type:**

Frequency and ratio and period average

**Frequency Range:**

+0.000/+512.000 megahertz multiple period and +0.000/+50.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+1.000 megahertz multiple period and +0.000/+0.300 megahertz multiple period

**Accuracy Rating:**

Porm 1 count and porm time base! Porm 1 count of f1 and porm trigger error of f2! Porm 1 count, porm time base, and porm trigger error

**Sensitivity Rating:**

F1 input 0.1v rms! F2 input 0.1v rms

**Ratio Display:**

F1/f2 times period multiplier

**Period Range:**

+1.0/+100000.0

**Period Range Step Quantity:**

6 decade steps

**Count Rate:**

10.000000 megahertz multiple period and 0.000001 megahertz multiple period and 10.000000 megahertz multiple period and 0.000001 megahertz multiple period

**Internal Calibration Feature:**

Included

**Display Type:**

Numeric readout tube

**Display Digit Quantity:**

8

**Display Units Indicator:**

Not included

**Display Positioned Decimal Point:**

Provided

**Display Storage Facility:**

Included

**Remote Control Provisions:**

Included

**Solid State Feature:**

Included

**Inclosure Material And Location:**

Steel case

**Inclosure Surface Treatment And Location:**

Enamel case

**Plug-in Units Provision:**

Included

**Standard Frequency Output Feature:**

Included

**Frequency Accuracy/stability:**

3 parts/1, 000, 000, 000/day

**Output Frequency Waveform:**

Rectangular wave

**Frequency Output Amplitude:**

5.0 volts peak to peak

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T297-a