

View Online at <https://aerobasegroup.com/nsn/6625-00-998-3437>

Circuit Current For Which Designed:

Dc

Overall Length:

4.500 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

60 single indicator all ranges

Frequency Rating:

Between 360.0 hertz and 440.0 hertz

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator 2nd range and red single indicator 2nd range

Accuracy In Percent:

-0.016/+0.016 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.750 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+900.0/+1200.0 microamperes, dc single indicator 2nd range

Scale Selection Method:

Switch

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

7 solder stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance on 0 to 1200 range: 150 ohms; on 900 to 1200 range resistance varies from 0 at 900 microamperes to 150 ohms at 1200 microamperes

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0