NSN 6625-00-999-5448

Digital Readout Electronic Counter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-999-5448 **Overall Length:** 16.375 inches Wattage Rating In Watts: 95.0 **Overall Height:** 5.250 inches **Overall Width:** 16.750 inches **Current Type:** Ac or dc Frequency Rating: 1.0 megahertz **Accessory Component Quantity: Electrical Connection Type: Internal Battery Accommodation:** Not included **Voltage Rating:** 115.0 volts and 230.0 volts **Output Frequency Rating:** 1.0 megahertz **Electrical Connection Quantity: Accessory Component Name:** Cable assembly, detachable power cord w/nema plug, printed circuit board extender, rack adapter kit **Measurement Type:** Frequency and period average and ratio Frequency Range: +0.000/+50.000 megahertz **Accuracy Rating:** Porm 1 count porm time base **Gate Time:** Between 0.0 seconds and 10.0 seconds **Sensitivity Rating:** 0.1 volt rms Ratio Display: F1/f2 times period multiplier **Period Range:**

+1.0/+1000000.0

Period Range Step Quantity:

5 decade steps

NSN 6625-00-999-5448

Digital Readout Electronic Counter - Page 2 of 2



Count Rate:
50.0 megahertz single period
Internal Calibration Feature:
Included
Display Type:
Numeric readout tube
Display Digit Quantity:
8
Display Units Indicator:
Included
Display Positioned Decimal Point:
Provided
Display Storage Facility:
Included
Remote Control Provisions:
Included
Solid State Feature:
Included
Inclosure Material And Location:
Aluminum body
Plug-in Units Provision:
Plug-in Units Provision:
_
Included
Included Standard Frequency Output Feature:
Included Standard Frequency Output Feature: Included
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single Shelf Life:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single Shelf Life: N/a
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single Shelf Life: N/a
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single Shelf Life: N/a Unit Of Measure:
Included Standard Frequency Output Feature: Included Frequency Accuracy/stability: 3 parts per 10000000000 per 24 hours Output Frequency Waveform: Rectangular wave and sine wave Frequency Output Amplitude: 1.0 volts peak to peak Phase: Single Shelf Life: N/a Unit Of Measure: Demilitarization: