

View Online at <https://aerobasegroup.com/nsn/6625-01-005-6584>

Circuit Current For Which Designed:

Ac

Overall Length:

2.530 inches

Mounting Hole Diameter:

0.138 inches

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

6.0 amperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.390 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

60 cps; 0; 25; 50; 75; 100; 125; 50 cps; percent of full load current; 0; 50; 100; 150

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Markings:

Sealed do not open ruggedized on back of meter

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0