

View Online at <https://aerobasegroup.com/nsn/6625-01-006-7936>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

4.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

4.312 inches

**Overall Width:**

4.312 inches

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

0.625 inches

**Furnished Items And Quantity:**

Nut 15; washer 15

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.687 inches

**Meter Body Diameter Behind Mounting Flange:**

3.968 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+300.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Max term. V to gnd 920 v peak

**Fsc Application Data:**

Text sets, electronic systems, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0