

View Online at <https://aerobasegroup.com/nsn/6625-01-007-2141>

Circuit Current For Which Designed:

Dc

Overall Length:

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Mounting Stud Length:

Between 0.500 inches and 0.750 inches

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

10.000 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+0.0/+50.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Style Designator:

Rectangular flush mtg

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0