

View Online at <https://aerobasegroup.com/nsn/6625-01-007-6785>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.625 inches

Overall Height:

4.125 inches

Overall Width:

5.000 inches

Mounting Hole Diameter:

0.203 inches

Scale Division Quantity:

100 single indicator single range

Mounting Bolt Circle Diameter:

1.750 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

3.156 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-100.0/+100.0 microamps single indicator single range

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Terminal resistance and tolerance at 25 degrees centigrade: 325 ohms plus or minus 20 percent

Fsc Application Data:

Test set, elect. Equip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0