

View Online at <https://aerobasegroup.com/nsn/6625-01-007-9957>

Overall Length:

570.000 millimeters

Overall Height:

197.000 millimeters

Overall Width:

335.000 millimeters

Current Type:

Ac or dc

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Accessory Components And Quantity:

Blue, light filter 1, front panel cover 1, vinyl storage pouch 1, power cord 1, manual 1

Voltage Rating:

Between 100.0 volts and 240.0 volts

Beam Quantity:

2

Graduation Interval:

Graduated in v/cm both axis

Accuracy Range In Percent:

-0.02/+0.02 or -0.06/+0.06 or -0.15/+0.15

Screen Size:

6 by 10 centimeters

Sweep Circuits:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.0/+275.0 megahertz

Trigger Sweep Voltage Amplitude Rating:

10.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

20 nsec and 50 usec

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

10.0 millivolts rms per centimeter and 5.0 volts rms per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

10.0 millivolts cw minor and 5.0 volts peak minor

Input Intensity Modulation Feature:

Provided

Frequency Response Rating:

Provided

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

3.0 volts

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g