

View Online at <https://aerobasegroup.com/nsn/6625-01-008-4453>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

1.346 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.074 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.620 inches

Mounting Hole Diameter:

0.086 inches

Scale Division Quantity:

2 single indicator single range

Overall Diameter:

1.455 inches

Environmental Protection:

Cold resistant and fungus proof and heat resistant and humidity proof and salt spray resistant and shock resistant and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-10.0/+10.0 at 1/2 scale single indicator single range

Meter Depth Behind Mounting Flange:

0.921 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black, dull single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

Center line; +

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Markings:

Center line on scale indicates 0

Material:

Aluminum alloy

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate and paint lusterless

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0