

View Online at <https://aerobasegroup.com/nsn/6625-01-009-0729>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

4.180 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.795 inches and 3.815 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.740 inches and 0.760 inches

Overall Height:

1.525 inches

Overall Width:

4.234 inches

Scale Division Quantity:

11 single indicator 1st range

Environmental Protection:

Dust resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.124 inches

Meter Body Width Behind Mounting Flange:

3.450 inches

Movement Type:

Moving magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+2.5 milliamperes, dc single indicator 1st range

Mounting Stud Diameter:

0.152 inches

Scale Selection Method:

Switch

Meter Body Height Behind Mounting Flange:

1.525 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0