

View Online at <https://aerobasegroup.com/nsn/6625-01-009-0729>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

4.180 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.795 inches and 3.815 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 0.740 inches and 0.760 inches

**Overall Height:**

1.525 inches

**Overall Width:**

4.234 inches

**Scale Division Quantity:**

11 single indicator 1st range

**Environmental Protection:**

Dust resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

3.124 inches

**Meter Body Width Behind Mounting Flange:**

3.450 inches

**Movement Type:**

Moving magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+2.5 milliamperes, dc single indicator 1st range

**Mounting Stud Diameter:**

0.152 inches

**Scale Selection Method:**

Switch

**Meter Body Height Behind Mounting Flange:**

1.525 inches

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0