

View Online at <https://aerobasegroup.com/nsn/6625-01-010-3968>

Overall Length:

2.100 inches

Overall Diameter:

0.310 inches

Environmental Protection:

Moisture proof

Vibration Resistance Range In Hertz:

+5.0/+15.0

Vibration Resistance Amplitude:

0.06 inches total excursion

Shock Resistance Rating In Gravitational Units:

15.0

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Cylindrical

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encased

Installation Design:

Module

Circuit Construction Type:

Solid state

Frequency Per Channel:

1.0 gigahertz operating channel err-100

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms input channel

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Dish, sherbet unthreaded universal fitting bolt end

Connection Contact Type And Quantity:

1 hyperboloid threaded male

Fsc Application Data:

Test set, receiver-transmitter group, countermeasures

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200