

View Online at <https://aerobasegroup.com/nsn/6625-01-011-7835>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.230 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.145 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

Overall Height:

2.885 inches

Overall Width:

3.005 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.515 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.3 ohms

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.315 inches

Meter Body Diameter Behind Mounting Flange:

2.145 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+500.0 milliamperes, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0