

View Online at <https://aerobasegroup.com/nsn/6625-01-013-4820>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.800 inches

**Overall Width:**

1.800 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

15 single indicator single range

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+1.5 amperes, dc single indicator single range

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 solder stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with mil-m-10304/24

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0