

View Online at <https://aerobasegroup.com/nsn/6625-01-013-8558>

Circuit Current For Which Designed:

Dc

Overall Length:

1.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.375 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.400 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Three scales: first scale-zero center goes from neg. 10.0 to pos 10.0 and neg 50.0 to pos 50.0; second scale-neg 7.0 to pos 3.0; third scale has 3 positions-16.4, 16.5 and 16.6

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

The second scale is non-linear; the third scale has 3 divisions

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0