

View Online at <https://aerobasegroup.com/nsn/6625-01-014-3859>

Overall Length:

19.000 inches

Overall Height:

7.718 inches

Overall Width:

20.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Joint Electronics Type Designation System Item Name:

Oscilloscope

Joint Electronics Type Designation System Item Type Number:

Os-230-p-urm

Voltage Rating:

Between 105.0 volts and 125.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in v/cm both axis

Mounting Method:

Rack

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

6 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal

Single Trigger Sweep Duration:

Between 1.0 microseconds and 50.0 seconds

Trigger Sweep Voltage Amplitude Rating:

Between 125.0 millivolts and 250.0 millivolts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

Marker intervals not indicated on screen

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

3.0 megahertz

Y-axis Frequency Response Rating:

100.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

Between 1.0 megohms and 10.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

Between 0.2 volts and 100.0 volts

Measurement Range Quantity:

2

Measurement Range Steps:

0.2 to 10.0 mv and 0.2 to 100.0 v

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g