

View Online at <https://aerobasegroup.com/nsn/6625-01-014-8114>

Circuit Current For Which Designed:

Dc

Overall Length:

1.525 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.126 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.115 inches

Overall Height:

1.754 inches

Overall Width:

1.752 inches

Mounting Hole Diameter:

0.114 inches

Scale Division Quantity:

2 single indicator single range

Environmental Protection:

Airtight and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 6; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1175.0 ohms

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

1.495 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

White lines 0.562 in. Long across

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Stamp on back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0