

View Online at <https://aerobasegroup.com/nsn/6625-01-015-1806>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.945 inches

**Overall Height:**

0.910 inches

**Overall Width:**

2.145 inches

**Mounting Hole Diameter:**

0.120 inches

**Environmental Protection:**

Cold resistant and dust resistant and heat resistant and humidity resistant and salt spray resistant and sand proof and shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

Between 1.899 inches and 1.913 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.456 inches

**Meter Body Width Behind Mounting Flange:**

1.710 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Yellow, fluorescent single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-10.0/+0.0 decibels above or below one watt single indicator single range

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

0.610 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 turret

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

5500 ohms resistance

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0