NSN 6625-01-017-0330

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-017-0330

Circuit Current For Which Designed:
Dc
Overall Length:
0.938 inches
Scale Division Quantity:
5 single indicator single range
Overall Diameter:
2.300 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Dial Scale Marking Color:
White single indicator single range
Meter Depth Behind Mounting Flange:
0.638 inches
Meter Body Diameter Behind Mounting Flange:
1.995 inches
Background Color:
Black single indicator single range
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 bracket
1 bracket
1 bracket Measurement Range:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Shelf Life:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Shelf Life: N/a
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Shelf Life: N/a
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
1 bracket Measurement Range: -15.0/+15.0 amperes, dc single indicator single range Circuit Attachment Method And Quantity: 2 threaded stud Material: Plastic Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: