

View Online at <https://aerobasegroup.com/nsn/6625-01-017-3526>

Circuit Current For Which Designed:

Dc

Overall Length:

1.120 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Locking ring 1, 0.03 in. Gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.810 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bushing and 1 threaded body

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+50.0 volts, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic polycarbonate

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0