NSN 6625-01-017-5378

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-01-017-5378

| Dc |
|---|
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 1.355 inches |
| Overall Height: |
| 1.640 inches |
| Overall Width: |
| 1.980 inches |
| Scale Division Quantity: |
| 20 single indicator single range |
| Environmental Protection: |
| Heat resistant |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Sensitivity Rating: |
| 1.0 amperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 0.810 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.360 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 snap slide |
| Scale Graduation Type: |
| Linear single indicator single range |

Measurement Range:

+0.0/+10.0 amperes, dc single indicator single range

NSN 6625-01-017-5378

Ammeter - Page 2 of 2



| Scale Selection Method: |
|---|
| Terminal |
| Features Provided: |
| External shunting and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base and taut band |
| Circuit Attachment Method And Quantity: |
| 2 screw and 2 solder lug |
| Special Features: |
| Tubular shaped pointer; 0.1 in. Tap internal multiplier |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Fan shape flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |