## NSN 6625-01-017-5380

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-017-5380

| Circuit Current For Which Designed:                   |
|---|
| Ac  |
| Indicator Type:                                       |
| Dial w/pointer  |
| Installation Design:                                  |
| Panel   |
| Dial Scale Marking Color:                             |
| Black single indicator single range                   |
| Accuracy In Percent:                                  |
| -2.0/+2.0 at full scale single indicator single range |
| Movement Type:  |
| Moving iron vane                                      |
| Background Color:                                     |
| White single indicator single range                   |
| Pointer Color:  |
| Black single indicator single range                   |
| Power Source:   |
| External  |
| Features Provided:                                    |
| Zero adjuster   |
| Movement Suspension Method:                           |
| Taut band   |
| Circuit Attachment Method And Quantity:               |
| 2 threaded stud                                       |
| Special Markings:                                     |
| D; c; amps on meter face                              |
| Nuclear Hardness Critical Feature:                    |
| Nonhardened   |
| Fsc Application Data:                                 |
| Test set, elect. Equip.                               |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
| -   |
| Demilitarization:                                     |
| No  |
| Filg:   |
| A310a0  |