Radio Frequency Detector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-017-8463

Our well to an article
Overall Length:
3.000 inches
Overall Diameter:
0.750 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+5.0/+33.0
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Cylindrical
Identification Designator:
G300272s1-24930
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
4.0 gigahertz operating channel err-100
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
50.0 milliwatts input
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
50.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds

NSN 6625-01-017-8463

Radio Frequency Detector - Page 2 of 2



Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial rear

Connection Contact Type And Quantity:

1 receptacle, coaxial external and 1 receptacle, coaxial external

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200