

View Online at <https://aerobasegroup.com/nsn/6625-01-018-1086>

**Circuit Current For Which Designed:**

Dc

**Reliability Indicator:**

Not established

**Overall Length:**

1.850 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

188.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

188.0 millimeters

**Overall Height:**

2.380 inches

**Overall Width:**

2.380 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

53.0 millimeters

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.340 inches

**Meter Body Diameter Behind Mounting Flange:**

2.160 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Measurement Range:**

+0.0/+5.0 amperes, dc single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0