

View Online at <https://aerobasegroup.com/nsn/6625-01-018-1086>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

1.850 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

188.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Width:

188.0 millimeters

Overall Height:

2.380 inches

Overall Width:

2.380 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

53.0 millimeters

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.340 inches

Meter Body Diameter Behind Mounting Flange:

2.160 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+0.0/+5.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0