

View Online at <https://aerobasegroup.com/nsn/6625-01-019-5496>

Circuit Current For Which Designed:

Dc

Overall Length:

3.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.795 inches and 3.815 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.742 inches and 0.758 inches

Overall Height:

1.310 inches

Overall Width:

4.234 inches

Mounting Hole Diameter:

0.138 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.144 inches

Meter Body Width Behind Mounting Flange:

3.450 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+100.0 millivolts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

Between 1.495 inches and 1.510 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 pin

Special Features:

Ruggedized

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0