

View Online at <https://aerobasegroup.com/nsn/6625-01-019-6650>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

6.890 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.560 inches

**Overall Height:**

4.270 inches

**Overall Width:**

4.710 inches

**Scale Division Quantity:**

60 single indicator 1st range

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Mounting Stud Length:**

0.500 inches

**Furnished Items And Quantity:**

Term. Lugs 17

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+50.000/+1000.000 hertz

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

5.500 inches

**Meter Body Diameter Behind Mounting Flange:**

2.790 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Upper scale reads fahrenheit; m 150; 0; 150; 300; 450; lower scale reads centigrade; m 100; 0; 100; 200

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Adjustable index pointer and zero adjuster

**Circuit Attachment Method And Quantity:**

17 screw

**Operating Voltage Rating In Volts:**

120.0 ac

**Special Features:**

Two adjustable index pointers

**Special Markings:**

Thermocouple copper

**Material:**

Plastic phenolic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic systems, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0