

View Online at <https://aerobasegroup.com/nsn/6625-01-019-6650>

Circuit Current For Which Designed:

Ac

Overall Length:

6.890 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.560 inches

Overall Height:

4.270 inches

Overall Width:

4.710 inches

Scale Division Quantity:

60 single indicator 1st range

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Term. Lugs 17

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+50.000/+1000.000 hertz

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

5.500 inches

Meter Body Diameter Behind Mounting Flange:

2.790 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Upper scale reads fahrenheit; m 150; 0; 150; 300; 450; lower scale reads centigrade; m 100; 0; 100; 200

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Mounting Stud Diameter:

0.138 inches

Features Provided:

Adjustable index pointer and zero adjuster

Circuit Attachment Method And Quantity:

17 screw

Operating Voltage Rating In Volts:

120.0 ac

Special Features:

Two adjustable index pointers

Special Markings:

Thermocouple copper

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic systems, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0