

View Online at <https://aerobasegroup.com/nsn/6625-01-020-6302>

Current Type:

Ac and dc

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Accessory Components And Quantity:

6 ft probes 2, blue crt light filter 1, clear crt light filter 1, ground post 1

Voltage Rating:

Between 12.0 volts and 240.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in 0.2 cm increments

Mounting Method:

Table

Screen Size:

8 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Not provided

Amplifier Input Impedance Rating Provision:

Not provided

Amplitude Calibrating Voltage Waveform:

Any acceptable

Calibrating Peak To Peak Amplitude:

0.3 volts

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g