

View Online at <https://aerobasegroup.com/nsn/6625-01-022-5261>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

Between 2.230 inches and 2.250 inches

Overall Height:

Between 3.490 inches and 3.510 inches

Overall Width:

Between 3.490 inches and 3.510 inches

Mounting Stud Length:

Between 0.490 inches and 0.510 inches

Mounting Bolt Circle Diameter:

Between 3.240 inches and 3.260 inches

Furnished Items And Quantity:

Nut 8; washer 10

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.240 inches and 1.260 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.870 inches and 2.890 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+80.0 amperes, ac single indicator single range

Mounting Stud Diameter:

Between 0.128 inches and 0.148 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Response time 2.5 seconds ; overload sustained 20 percent for eight hours

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0