

View Online at <https://aerobasegroup.com/nsn/6625-01-022-5261>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

Between 2.230 inches and 2.250 inches

**Overall Height:**

Between 3.490 inches and 3.510 inches

**Overall Width:**

Between 3.490 inches and 3.510 inches

**Mounting Stud Length:**

Between 0.490 inches and 0.510 inches

**Mounting Bolt Circle Diameter:**

Between 3.240 inches and 3.260 inches

**Furnished Items And Quantity:**

Nut 8; washer 10

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

Between 1.240 inches and 1.260 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.870 inches and 2.890 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+80.0 amperes, ac single indicator single range

**Mounting Stud Diameter:**

Between 0.128 inches and 0.148 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Response time 2.5 seconds ; overload sustained 20 percent for eight hours

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0