

View Online at <https://aerobasegroup.com/nsn/6625-01-022-5264>

Circuit Current For Which Designed:

Ac

Overall Length:

Between 3.010 inches and 3.030 inches

Overall Height:

3.510 inches

Overall Width:

3.510 inches

Mounting Stud Length:

0.500 inches

Mounting Bolt Circle Diameter:

3.250 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

5

Accuracy In Percent:

-0.3/+0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.320 inches

Meter Body Diameter Behind Mounting Flange:

2.760 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Measurement Range:

+59.0/+63.0 hertz single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Impedance 16.5 kilohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0