NSN 6625-01-023-0500

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-023-0500

Overall Length:
19.250 inches
Overall Height:
5.250 inches
Overall Width:
19.000 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 400.0 hertz
Voltage Rating:
220.0 volts
Beam Quantity:
1
Graduation Interval:
Graduated in 1/2 in./div
Mounting Method:
Rack
Screen Size:
6.5 in. By 6.5 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+0.0/+1.0 megahertz
Trigger Sweep Polarity Switch:
Included
Amplifier Deflection Sensitivity Provision:
Provided
Input Intensity Modulation Feature:
Provided
Visual Modulation Sensitivity Voltage Rating:
5.0 volts
Visual Blanking Sensitivity Voltage Rating:
5.0 volts
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
2.0 megahertz

2.0 megahertz

NSN 6625-01-023-0500

Oscilloscope - Page 2 of 2



Y-axis Frequency Response Rating:
2.0 megahertz
Z-axis Frequency Response Rating:
1.0 megahertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
250.0 kilohms
Y-axis Input Impedance Rating:
250.0 kilohms
Z-axis Input Impedance Rating:
10.0 kilohms
Amplitude Calibrating Voltage Waveform:
Square wave
Calibrating Peak To Peak Amplitude:
400.0 millivolts
Calibrated Screen Scale:
Included
Trace Storage Tube:
Included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T320-g